MOTOR OILS **SM Multigrade**

Description: **Shellbourne's SM Series Motor Oils**, are available in four multigrade and six single-viscosity grade formulations. These oils meet the latest automotive and light duty truck manufacturer's requirements. Shellbourne's Motor Oils utilize high quality virgin base oils combined with the latest in additive technology. These products provide the highest levels of equipment protection available.

Usage: **Shellbourne's SM Motor Oils** are generally used in gasoline and light duty diesel engine applications. The product is available in 5W20, 5W30, 10W30, 10W40, and 20W50 viscosity grades. Users should follow equipment manufacturer recommendations for specific applications.

Typical Properties:

Kinematic	5W20	5W30	10W30	10W40	20W50
Viscosity, cST @ 40 degrees	48.2	65.9	71.7	98.6	112.3
@ 100 degrees	8.4	11.2	10.76	14.68	18.09
Viscosity Index	151	164	139	155	124
Cold Crank (Brookfield)	3020@-25C	3060@-25C	3240@-20C	3190@-20C	4040@-10
Pour Point degrees C					
Density @ 15 degrees C,kg/m3	.868	.87	.878	.874	.876

Application: **Shellbourne's Motor Oils** may be recommended for the following applications:

When SM,SJ, SH,SF,SE, SD, or SC oils are required
When GM 4718M/6094 and Ford M2C153-E oils are required
When Energy Conserving motor oil is specified (5W20,5W30,10W30)
Meets domestic and foreign car manufacturer's requirements

Product Features:

* Excellent protection from deposits at all operating temperatures
* Excellent bearing corrosion protection
* Excellent anti-wear, anti-foam and anti-rust properties
* Excellent cold cranking capabilities